



Recommend PCB Layout
Tolerance: ±0.05

1. MATERIAL:
 - 1.1. Housing: HH-TEMP Plastic, U94V-0, black;
 - 1.2. Terminal: Coppy alloy, T=0.12mm
 - 1.3. Latch: Stainless steel T=0.12mm
2. FINISH:
 - 2.1 Terminal: Plated Au on contact area, matte tin on the solder tails underplated nickel over all.
 - 2.2 Latch: 120U" Min matte tin over nickel,
3. Electrical Performance:
 - 3.1 Contact Resistance: 50mΩ Max;
 - 3.2 Dielectric Withstanding Voltage: 350V AC rms for 1 minut;
 - 3.3 Insulation Resistance: 1000 MΩ Min;
4. Mechanical Performance:
 - 4.1 Durability: 5000 cycles;
 - 4.2 Normal force: 60gf Min;

GENERAL TOLERANCE		DWG NO.	JYSA1126-02	APPD.	WMD	Scale	1:1
X.±0.45	X.±5'	Title	BATTERY 3PIN 3.0PITCH 1.5H	CHKD:		UNIT	mm
X.±0.35	X.±2'	Pprt NO.	JYS-BY150-095	DR:			
.XX±0.25	.xx±1'	Date	2012/02/29				
.XX±0.15	.xxx±0.5'						
SHEET	1/1						


 杰宇森电子有限公司
 JIE YU SEN ELECTRONIC CO., LTD.

REV.	EQUNO.	MODIFY/CONTENT	DATE
A		NEW	2011/10/31