



热稳定性 Specifications:  
电气特性 Electrical:

- 1. 额定电流: Current Rating  
1.5A/contact terminal
- 2. 额定电压: Voltage Rating  
30V DC
- 3. 接触电阻: Contact Resistance  
30 milliohms MAX
- 4. 耐电压: Dielectric Withstanding Voltage:  
500 V AC AT Sea Level
- 5. 绝缘电阻: Insulation Resistance:  
1000MEGA ohms MIN

物理性能 Mechanical:

- 1. 插拔力: Connector Mate and Unmate Force  
Mate force: 3.57kgf (MAX)  
Unmate force: 1.02kgf (MIN)
- 2. 端子保持力: Terminal Retention  
1.2kgf (MIN)

原材料 Material:

- 1. 塑胶: Housing:  
Hing Temperature Ternmaplastics,  
Ul 94V-0 PBT White/Black
  - 2. 端子接触: Copper Alloy C2680
  - 3. 外壳: Shell: Copper Alloy C2680/SPCC
- 电镀 Finish:  
1. 端子接触: Plated Gold in Mating Area;  
Tin On Solder Tails  
2. 外壳: Shell:  
Nickel Plating

GENERAL TOLERANCE		DWG NO.	APPD:	WIND	Scale	1:1
X±0.45	X:±5°	JYSA0804-001	CHKD:		UNIT	mm
X±0.35	X:±2°		DR:			
.XX±0.25	.XX'±1°	JYS-USB140-021	Date	2012/04/13		
.XXX±0.15	.xxx'±0.5°					
SHEET 1/1						

REV.	EQN.NO.	MODIFY CONTENT	DATE
A		NEW	2012/04/13